

SAFEBOARD™

HYBRID ADHESIVE

WHAT IS SAFEBOARD™?

Made in the USA, SAFEBOARD™ was specifically designed to bond SAFEBOARD™ to other substrates. SAFEBOARD™ uses hybrid technology to develop immediate strength to substrates while the adhesive cures, and provides a long-term, durable bond. Made up of 100% solids, SAFEBOARD™ will not shrink and is free of isocyanates and solvents which make it easy and friendly to work with at a variety of temperatures. SAFEBOARD™ will remain consistent to dispense and tool whether cold or hot outside unlike many solvent based adhesives. It will bond to wet substrates and can be applied when water or moisture is present without washing off (water based adhesives) or outgassing and bubbling (polyurethanes). SAFEBOARD™ has a very broad adhesion range and can be used for a variety of industrial or construction applications.

WHY USE SAFEBOARD™?

With solvent based adhesives, the solvent flashes off during curing. Water based adhesives have water loss during curing. This can often leave behind just 60% of what you applied. With SAFEBOARD™, what you apply stays, which can reduce adhesive usage.

A lot of adhesives that are eco-friendly do not have the strength required for the job. SAFEBOARD™ offers an eco-friendly option that is also made to perform.

SAFEBOARD™ has excellent strength and fixturing properties. It not only bonds well to a variety of substrates, but it also grabs and holds which helps reduce assembly time, brace usages, fastener usage, and more.

COMMON BONDING SUBSTRATES

- SAFEBOARD™ Aluminum
- SAFEBOARD™ Composite
- Natural Stone
- Engineered Stone
- Porcelain
- Galvanized Metal
- Fiberglass
- Glass
- Wood
- PVC & other plastics
- Concrete, Brick, and more



Can be used on additional substrates not listed. SAFEBOARD™ can be used on a variety of substrates. Please inquire or test your substrates before use. Substrates may vary with manufacturer.



SAFEBOARD™

HYBRID ADHESIVE

CONFORMS, MEETS, AND EXCEEDS:

- CONFORMS TO CALIFORNIA PROPOSITION 65
- CONFORMS TO USDA REQUIREMENTS / NON-FOOD CONTACT
- MEETS REQUIREMENTS OF CARB & SCAQMD
- VOC COMPLIANT (9.55 GRAMS/LITER ASTM D2369)

FEATURES:

- NO SOLVENTS OR WATER, WILL NOT SHRINK
- 100% SOLIDS, VOC COMPLIANT
- OFFERS IMMEDIATE GREEN STRENGTH
- ADHERES TO A WIDE VARIETY OF SUBSTRATES
- REMAINS EASY TO DISPENSE FROM 0-150F
- CURES TO WET SUBSTRATES OR WHEN MOISTURE IS PRESENT
- REMAINS FLEXIBLE, ALLOWS FOR VIBRATION AND MOVEMENT

Limitations

Do not store at elevated temperatures. Use only on clean surfaces free of contaminants. Cold temperature and low humidity will slow curing (32°F and below will be most significant). Do not use on olefins such as polyethylene, polypropylene or TPO prior to testing. Test all paints before application. Allow treated wood and asphalt to cure 6 months before application. Long-term submersion under water can cause loss of adhesion on some substrates.

Warranty Limitations

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain such authorization. Because the storage, handling and application of the material is beyond ASI's control, we can accept no liability for the results obtained. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted. Suggestions of uses should not be taken as inducements to infringe upon any patents.

